

HANSEN PRESSURE-RELIEF VALVE CAPACITIES [kg/hr, (air)]

Set point (kPa)	1/2"x3/4"FPT H5600R H5602R 3/4"x1"FPT	3/4"x1"FPT H5632R	1"x1 1/4"FPT H5633R	1 1/4"x1 1/2"FPT H5634R	1/2"x3/4"FPT H5600A	1/2"x 1"FPT H5601 H5602 3/4"x1"FPT	1"x1 1/4"FPT H5613	1 1/4"x1 1/2"FPT H5604
K _{dr}	0.913	0.866	0.832	0.844	0.755	0.697	0.752	0.691
1030	287	598	770	913	848	971	1439	1955
1100	305	635	818	970	901	1032	1529	2077
1200	330	689	887	1051	977	1119	1657	2251
1300	356	742	956	1133	1052	1205	1786	2425
1400	381	795	1024	1214	1128	1292	1914	2600
1500	407	849	1093	1296	1203	1379	2042	2774
1600	433	902	1162	1377	1279	1465	2171	2948
1700	458	955	1230	1458	1355	1552	2299	3123
1800	484	1009	1299	1540	1430	1638	2427	3297
1900	509	1062	1368	1621	1506	1725	2556	3472
2000	535	1115	1436	1703	1582	1812	2684	3646
2100	560	1169	1505	1784	1657	1898	2812	3820
2200	586	1222	1574	1866	1733	1985	2941	3995
2300	612	1275	1642	1947	1809	2072	3069	4169
2400	637	1329	1711	2028	1884	2158	3198	4343
2500	663	1382	1780	2110	1960	/	3326	4518
2600	688	1436	1849	2191	2036		3454	4692
2700	714	1489	1917	2273	2111		3583	4867
2760	729	1521	1959	2322	2157		3660	4971

HANSEN TECHNOLOGIES CORP. BURR RIDGE, IL. USA 8/9/2005

Pressure settings between above listed set points can be supplied as required.

The “**R**” type are the reduced capacity range, (special order) The “standard” range (selected stock held), capacities shown in **Bold**.

WARD VALVE & CONTROL PTY LTD P O Box 45, Vermont, Vic. 3133 Tel: 03 9873 7222 Fax: 03 9873 7221