

# INTENSIFIA™

## DEEP ENHANCEMENT & STAIN PROTECTION

Deep, long lasting color enhancement and premium stain protection for porous surfaces, including natural stone, brick, paving and masonry



- Provides deep color enhancement
- Premium oil and water based stain protection\*\*
- Easy to apply
- Breathable: water vapor permeates freely, avoiding moisture build-up inside the material
- Retains wet slip resistance of porous flooring material
- Suitable for indoor, outdoor, residential and commercial use
- 5 year warranty\*

### INTENSIFIA™ WILL PROTECT:

- |                   |                    |
|-------------------|--------------------|
| ■ Basalt          | ■ Marble           |
| ■ Brick           | ■ Quarry tiles     |
| ■ Cement pavers   | ■ Saltillo tiles   |
| ■ Clay pavers     | ■ Sandstone        |
| ■ Concrete        | ■ Slate            |
| ■ Encaustic tiles | ■ Terracotta tiles |
| ■ Granite         | ■ Terrazzo         |
| ■ Grout           | ■ Travertine       |
| ■ Limestone       |                    |



# BASIC SEALING GUIDE

## BEFORE SEALING:

- Surfaces must be thoroughly clean and dry before applying a sealer. Once sealed, the surface becomes water repellent, making it tough to remove existing stains.

## ALL YOU WILL NEED:

- INTENSIFIA™
- Low pressure hand spray/lamb's wool applicator/brush
- Sufficient white absorbent cloths/towels
- Safety gear (gloves, protective eyewear, mask or chemical respirator if in a confined space)

## SEALING IN 5 EASY STEPS: (Refer to the back of the label for more information)



- 1. TEST:** Test product on a small area of the surface, wait 24 hours, and ensure you are satisfied with the results.



- 4. REMOVE EXCESS:** Before the first coat dries, thoroughly polish off all residue with clean, dry cotton cloths / towels, then let the product cure for at least an hour.



- 2. CLEAN:** Make sure the area to be treated is clean, dry and free of residues or topical coatings.



### 5. SECOND COAT:

Repeat steps 3 and 4. A third coat may be required for premium stain protection on extremely porous surfaces. Ensure that all residue are thoroughly polished off.



- 3. FIRST COAT:** Generously saturate the surface with INTENSIFIA™ using a lamb's wool applicator / brush / pump spray. Leave to penetrate for at least 30 minutes.

*Note: Surface can be walked on 2-3 hours after application. Do not get the surface wet for at least 8-10 hrs.*

## MAINTAINING YOUR SEALED SURFACE:

Dry-Treat has developed specialist cleaners under the HANAFINN™ brand to clean and maintain your natural stone surface.



**HANAFINN  
Oxy-Klenza™**  
for outdoor surfaces  
and stain removal



**HANAFINN  
Rejuvenata™ Active**  
for indoor surfaces  
and stain removal



**HANAFINN  
Rejuvenata™ Spray**  
for daily  
countertop cleaning



**HANAFINN  
Eff-Erayza™**  
for removing of efflorescence,  
rust marks and grout haze

For advanced application guide and complete guide on how to maintain your sealed surface, visit:

[www.drytreat.com/quickdocs.html](http://www.drytreat.com/quickdocs.html)