

STAIN-PROOF™

PREMIUM IMPREGNATING SEALER



World leading protection for natural stone, tile, paving and grout



- Premium stain protection**
- Protects against efflorescence, freeze-thaw and salt damage (Highly porous materials require Dry-Treat 40SK for freeze-thaw/salt protection)
- Breathable: water vapor permeates freely, avoiding moisture build-up inside the material
- Treated surfaces are easier to clean
- Retains wet slip resistance, existing color and finish
- Suitable for indoor, outdoor, residential and commercial use
- Provides long lasting protection and comes with 15 year warranty*

STAIN-PROOF™ will protect:

- | | |
|-------------------|--------------------|
| ■ Basalt | ■ Marble |
| ■ Brick | ■ Quarry tiles |
| ■ Cement pavers | ■ Saltillo tiles |
| ■ Clay pavers | ■ Sandstone |
| ■ Concrete | ■ Slate |
| ■ Encaustic tiles | ■ Terracotta tiles |
| ■ Granite | ■ Terrazzo |
| ■ Grout | ■ Travertine |
| ■ Limestone | |



STAIN-PROOF™ Plus
for extremely dense countertop materials

BASIC SEALING GUIDE

BEFORE SEALING:

- Surfaces must be thoroughly clean and dry before applying a sealer. Once sealed, the surface becomes water repellent, making it tough to remove existing stains.

ALL YOU WILL NEED:

- STAIN-PROOF™
- Low pressure hand spray/lamb's wool applicator/brush
- Sufficient white absorbent cloths/towels
- Safety gear (gloves, protective eyewear, mask or chemical respirator if in a confined space)

SEALING IN 5 EASY STEPS: (Refer to the back of the bottle for more information)



1. TEST: Test product on a small area of the surface, wait 24 hours, and ensure you are satisfied with the results.



2. CLEAN: Make sure the area to be treated is clean, dry and free of residues or topical coatings.



3. FIRST COAT: Generously saturate the surface with STAIN-PROOF™ using a lamb's wool applicator / brush / pump spray. Leave to penetrate for at least 10 minutes.



4. SECOND COAT: Before the first coat dries, apply a second generous coat of STAIN-PROOF™. Leave to penetrate again for at least 10 minutes.



5. REMOVE EXCESS: Before the second coat dries, **thoroughly polish off** all residue with clean, dry white cloths / towels. If the residue has been left too long, moisten a cloth with STAIN-PROOF™ to ease removal and polish off with dry cloths / towels.

Note: Surface can be walked on 2-3 hours after application. Do not get the surface wet for at least 8-10 hrs.

MAINTAINING YOUR SEALED SURFACE:

Dry-Treat has developed specialist cleaners under the HANAFINN™ brand to clean and maintain your natural stone surface.



**HANAFINN
Oxy-Klenza™**
for outdoor surfaces
and stain removal



**HANAFINN
Rejuvenata™ Active**
for indoor surfaces
and stain removal



**HANAFINN
Rejuvenata™ Spray**
for daily
countertop cleaning



**HANAFINN
Eff-Erayza™**
for removing of efflorescence,
rust marks and grout haze

For advanced application guide and complete guide on how to maintain your sealed surface, visit:

www.drytreat.com/quickdocs.html