



Ammeraal

Conveyor Belting

An AMMEGA Group Brand

Phone: 03 9794 8870

Fax: 03 9794 7708

Email: AU-Ammeraal@ammega.com

AMMERAAL AMRA 20DE 55 Shore D Polyester

APPLICATIONS

- Use in high contamination environments
- Cheese, milk, meat and poultry industries
- Wet applications where cleaning is required: fruit, vegetables, flower growers and handlers

CONSTRUCTION

Homogeneous 55 Shore D, synthetic material. Meets FDA Requirements. USDA approved

Top surface: gloss **Bottom surface:** low friction, diamond profile.

CHARACTERISTICS

- Ammeraal Amra 20 DE is available in either Blue or Ivory
- Highly sanitary, non-porous
- 100% non-fraying
- Low stretch, low noise and easy to clean with water up to 100°C
- Meets F.D.A requirements for contact with dry & bulk foods (Regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation

TECHNICAL DATA

Thickness:	2.0mm
Weight:	2.3kg/m ²
Max width:	1300mm
Min Pulley:	70mm (180° wrap)
Joining:	Mirror Welded, welding rod, fasteners
Belt Support:	UHMWPE deck or rollers
Work Load:	2.3N/mm will result in 1% elongation
Temp:	Operating: -20°C to +70°C Cleaning: +100°C

The above information is applicable at 15°C. To allow for ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.