

Phone: 03 9794 8870 Fax: 03 9794 7708

Email: belts@ammeraal.com.au

# AMMERAAL AMRA 20 55 Shore D Polyester

#### **APPLICATIONS**

- Use in high contamination environments.
- Cheese, milk, meat and poultry industries
- Wet applications where cleaning is required: fruit, vegetables, flower growers and handlers

## CONSTRUCTION

Homogeneous 55 Shore D, synthetic material. Meets FDA requirements. USDA approved

**Top surface:** gloss **Bottom surface**: satin

#### **CHARACTERISTICS**

- Ammeraal Amra 20 available in either blue or ivory
- Highly sanitary, non-porous.
- 100% non-fraying
- Low stretch, low noise and easy to clean with water up to 100°C
- Meets F.D.A requirements for contact with dry & bulk foods (Regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation.
- Odour and taste free, has excellent resistance to oil, fats and is UV stable

## **TECHNICAL DATA**

**Thickness:** 2.0mm

Weight: 2.4kg/m<sup>2</sup>

Max width: 1300mm

**Min Pulley:** 70mm (180° wrap) 50mm (120° wrap)

**Joining:** Mirror Welded, welding rod, fasteners

**Belt Support:** UHMWPE deck or rollers

**Work Load:** 2.4N/mm will result in 1% elongation

**Temp:** Operating: -20°C to +70°C Cleaning: +100°C

The above information is applicable at 15°C. To allow or ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.