



# Ammeraal

Conveyor Belting

An AMMEGA Group Brand

Phone: 03 9794 8870

Fax: 03 9794 7708

Email: AU-Ammeraal@ammega.com

## AMMERAAL AMRA 60DE 55 Shore D Polyester

### APPLICATIONS

- Use in high contamination environments.
- Cheese, milk, meat and poultry industries
- Wet applications where cleaning is required: fruit, vegetables, flower growers and handlers

### CONSTRUCTION

Homogeneous 55 Shore D, synthetic material. Meets FDA requirements. USDA approved

**Top surface:** gloss

**Bottom surface:** low friction, diamond profile

### CHARACTERISTICS

- Ammeraal Amra 60 DE available in either blue or ivory
- Highly sanitary, non-porous.
- 100% non-fraying
- Easy to join using low cost equipment.
- Meets F.D.A requirements for contact with dry & bulk foods (Regulation No.21CFR 177-1590) and fatty & wet foods (Regulation No.CFR 177-2600)
- No foreign matter is included in formulation.
- Odor and taste free, has excellent resistance to oil, fats and is UV stable

### TECHNICAL DATA

**Thickness:** 6.0mm

**Weight:** 7.0kg/m<sup>2</sup>

**Max width:** 1300mm

**Min Pulley:** 210mm (180° wrap)

**Joining:** Mirror Welded, welding rod, fasteners

**Belt Support:** UHMWPE deck or Rollers

**Work Load:** 7.8N/mm will result in 1% elongation

**Temp:** **Operating:** -20°C to +70°C **Cleaning:** +100°C

The above information is applicable at 15°C. To allow for ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.