



Ammeraal

Conveyor Belting

An AMMEGA Group Brand

Phone: 03 9794 8870

Fax: 03 9794 7708

Email: AU-Ammeraal@ammega.com

AMMERAAL BB20DE 95 Shore A PU

APPLICATIONS

- Use in high contamination environments.
- Processing applications like cheese, milk, meat and poultry industries
- Dough carrying and dough cutting application.
- High wear application such as Brick and Tile Industry, Timber, Steel processing accumulation

CONSTRUCTION

Homogeneous, 95 Shore A PU. Meets FDA requirements, USDA Approved

Top surface: gloss **Bottom surface:** low friction, diamond profile

CHARACTERISTICS

- Ammeraal Big Bear 20 DE, available in Blue or Ivory
- Highly sanitary, cut resistant, abrasive resistant, oil resistant, non-porous
- Low noise, easy to clean
- 100% non-fraying.
- Oil and grease resistant, easy to clean surfaces.
- Meets F.D.A requirements for contact with dry & bulk foods (regulation No. CFR 177-1680) and fatty and wet foods (Regulation No. CFR 177-2600).
- USDA Dairy and USDA Meat and Poultry approved
- No foreign matter is included in formulation.

TECHNICAL DATA

Thickness:	2.0mm
Weight:	2.3kg/m ²
Max width:	1300mm
Min Pulley:	30mm (180° wrap)
Joining:	Mirror Welded, welding rod, Fasteners
Belt Support:	UHMWPE deck or Rollers
Work Load:	1.2N/mm will result in 1% elongation
Temp:	-20°C to +70°C

The above information is applicable at 15°C. To allow for ongoing product developments this data is subject to alterations without prior notice. This information replaces that included in previous publications.