



504 SUITE
LANGFORD SLIDING
WINDOW

Sliding windows are neat, simple, reliable and attractive. With their smooth operation, these windows are a popular choice when large openings are required.



PRODUCT FEATURES

Custom made sizes to suit your requirements.

A true 50mm frame, suitable for most residential applications.

All windows come with key locks as standard with a variety of lock options and hardware colours including colour match powdercoat. Optional ventilation locates allow the sash to be locked in the closed or partially open position.

Centre opening sliders can be fitted with sliding flyscreens, ideal as a service window.

The suite is designed to carry a variety of glass types for sound reduction and temperature control, including double glazed.

These windows are certified up to BAL40 bushfire level.

For further information please contact the office



PRODUCT OPTIONS

ENERGY



The following table lists some of the typical WERS rated glass and frame combinations for this window type. For a complete list of all rated glass and frame combinations please contact the office

Glass Type	COOLING	HEATING	U Value	SHGC
4mm Clear	13%	17%	6.4	0.72
5mm Grey	30%	9%	6.4	0.53
6.38mm Comfort Plus Clear	35%	37%	4.5	0.59
6.38mm Comfort Plus Neutral	46%	28%	4.6	0.44
Double Glazed Clear - Clear / air / Clear	37%	40%	4.2	0.58
Double Glazed Low E - Clear / air / Low E clear	43%	44%	3.7	0.54

GENERAL	HARDWARE	WEATHER
<p><u>Max window height</u> 1500 - add a highlight or a lowlite to increase the size</p> <p><u>Max window width</u> Configuration dependent</p> <p><u>Max glass thickness</u> 18mm</p> <p><u>Frame depth</u> 50mm</p>	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Standard Handle</p> </div> <div style="text-align: center;">  <p>Vent Lock Handle</p> </div> </div>	<p><u>Max water rating</u> 450Pa</p>

For further information please contact the office