



548 SUITE  
LANGFORD BIFOLD  
DOOR

Our high performance Bifold Door can open up an entire wall in your home, making it an excellent choice for connecting the indoors to the outdoors.



## PRODUCT FEATURES

Custom made sizes to suit your requirement's. The architectural frame give the door a high wind and water rating. They feature wide top and bottom rails that give the doors a chunky appearance similar to timber designs.

Rebated door stiles give a flush appearance when the two doors meet and provide superior weather protection.

A large variety of combinations are available, stacking in either direction or biparting. These doors can be screen using Centor retractable screens.

They are designed to carry a variety of glass types for sound and temperature control, including double glazed. ClearVent Sashless double hung windows can be inlaid into the door sash to allow ventilation whilst the door is closed.

All doors come with key locks as standard with a variety of lock options and hardware colours including stainless steel or colour match powdercoat. They supported on quad rollers running on heavy duty bottom rails.

The sills can be recessed into the floor to create a seamless flow from inside to out.

Certified up to BAL40 bushfire rating

For further information please contact the office

LANGFORD WINDOWS | 12 Mitchell Rd, Cardiff | [sales@langfordwindows.com.au](mailto:sales@langfordwindows.com.au) | (02) 4953 5000







PRODUCT OPTIONS

ENERGY



The following table lists some of the typical WERS rated glass and frame combinations for this window type. For a complete list of all rated glass and frame combinations please contact the office

Glass Type	COOLING	HEATING	U Value	SHGC
5mm Clear	29%	15%	6.1	0.57
5mm Grey	39%	8%	6.1	0.43
6.38mm Comfort Plus Clear	44%	30%	4.6	0.47
6.38mm Comfort Plus Neutral	51%	24%	4.6	0.36
4mm/10/4mm Clear Double Glazed	42%	35%	4.3	0.51
6.38mm Comfort Plus Clear/ 8 /4mm clear Double Glazed	51%	35%	3.9	0.42

GENERAL	HARDWARE	WEATHER
<p><b>Max window height</b> 2700</p> <p><b>Max window width</b> 900 per door sash</p> <p><b>Max glass thickness</b> 20mm</p> <p><b>Frame depth</b> 102mm</p>	<div></div> <p>Miro Lever LockMiro Lever Operator Ando Lever Lock Ando Lever ICON Lever ICON Lever</p>	<p><b>Max water rating</b> 300Pa</p>



For further information please contact the office