

548 SUITE LANGFORD BIFOLD WINDOW

Our high performance Bifold window can open up an entire wall in your home, making it an excellent choice for a server or opening up a view.



PRODUCT FEATURES

Custom made sizes to suit your requirement's. The architectural frame give the door a high wind and water rating.

A large variety of combinations are available, stacking in either direction or biparting. These doors can be screen using Centor retractable screens.

They are designed to carry a variety of glass types for sound and temperature control, including double glazed. ClearVent Sashless double hung windows can be inlaid into the door sash to allow ventilation whilst the door is closed.

All windows come with key locks as standard with a variety of lock options and hardware colours including stainless steel or colour match powdercoat.

The sills can be recessed into the bench to create a seamless flow from inside to out.

PRODUCT OPTIONS

ENERGY



The following table lists some of the typical WERS rated glass and frame combinations for this window type. For a complete list of all rated glass and frame combinations please contact

| Glass Type | COOLING | HEATING | U Value | SHGC |
|---|---------|---------|---------|------|
| 5mm Clear | 29% | 15% | 6.1 | 0.57 |
| 5mm Grey | 39% | 8% | 6.1 | 0.43 |
| 6.38mm Comfort Plus Clear | 44% | 30% | 4.6 | 0.47 |
| 6.38mm Comfort Plus Neutral | 51% | 24% | 4.6 | 0.36 |
| Double Glazed Clear - Clear / air / Clear | 42% | 35% | 4.3 | 0.51 |
| Double Glazed Low E - Clear / air / Low E clear | 51% | 35% | 3.9 | 0.42 |
| | | 1 | 1 | 1 |

| GENERAL | HARDWARE | WEATHER |
|--|---|------------------------|
| Max window height 2700 Max window width 900 per door sash Max glass thickness 20mm Frame depth 102mm | Miro Lever LockMiro Lever Ando Lever Ando Lever ICON Lever Coperator Lock | Max water rating 300Pa |