












SELECTING YOUR PRODUCT

Roofing/Cladding	Page	BMT mm	TCT mm	Cover Width	Weight kg/m ²	Minimum Pitch	Roof Span*		Wall Span*	
							Int Span mm	End Span mm	Int Span mm	End Span mm
Stramit® Corrugated 	18	0.42	0.47	762	4.35	5 Degrees (1 in 12)	1200	1000	2650	2200
		0.48	0.53	762	4.93		1600	1300	2850	2350
Guide Only – Fixing Screws required per metre square = 5 For Premium Finishes refer page 59										
Stramit® Curving Quality 	20	0.60	0.65	762	6.09	-	1200	1000	3000	2500
		Guide Only – Fixing Screws required per metre square = 5 For Premium Finishes refer page 59								
Stramit Monoclad® 	22	0.35†	0.40	762	3.59	-	-	-	1800	1500
		0.42	0.47	762	4.35	2 Degrees	1700	1400	3000	2500
		0.48	0.53	762	4.93	(1 in 27)	2300	1900	3000	2500
Guide Only – Fixing Screws required per metre square = 5										
Stramit Longspan® 	24	0.42	0.47	700	4.73	1.5 Degrees (1 in 45)	2100	1750	3000	2500
		0.48	0.53	700	5.37		2700	2250	3000	2500
Guide Only – Fixing Screws required per metre square = 5 For Premium Finishes refer page 59										
Stramit Megaclad® 	24	0.42	0.47	800	4.14	2 Degrees (1 in 27)	1500	1250	2450	2000
		0.48	0.53	800	4.70		1800	1500	2600	2150
Guide Only – Fixing Screws required per metre square = 4										
Stramit Speed Deck Ultra® 	25	0.42	0.47	700	4.73	1 Degree (1 in 60)	2100	1750	3000	2500
		0.48	0.53	700	5.41		2700	2250	3000	2500
Guide Only – Fixing Clips required per metre square = 1.5 For Premium Finishes refer page 59										
Stramit K-Panel® 	26	0.35†	0.40	864	3.17	-	-	-	1500	1250
		0.42†	0.47	864	3.84	-	-	-	1700	1400
(Vertical garage cladding) Guide Only – Fixing Screws required per metre square = 5										
Stramit Minirib® 	26	0.35†	0.40	900	3.05	-	-	-	550	450
		0.42†	0.47	900	3.68	-	-	-	1500	1250
Guide Only – Fixing Screws required per metre square = 5 For Premium Finishes refer page 59										
Stramit Mini Corry® 	26	0.42†	0.47	825	4.01	-	-	-	1200	1000
		0.48†	0.53	825	4.56	-	-	-	1200	1000
Guide Only – Fixing Screws required per metre square = 5										
Stramit Monopanel® 	27	0.48†	0.53	250	4.68	-	-	-	3000	2500
Stramit Sunset® (Patio Decking) 	28	0.42	0.47	290	5.53	-	-	-		

**Non trafficable spans up to 4m

TCT = Total Coated Thickness. This is a nominal dimension. It should not be used in specifications due to variances in Coating and paint finish.
BMT = Base Metal Thickness. This is thickness of steel only and together with minimum yield strength and rolled profile provides the basis for calculation of the structural needs of a system. It should be referred to in specifications followed by the letters BMT.

† NOT suitable for roofing or cyclonic conditions.

* For N1 wind conditions and normal duty foot traffic.

* Masses are for Colorbond.