OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024

Reviewed on 05/01/2024

### 1 Identification

- · Product identifier
- · Trade name: Super Slick 'Em
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Product description

PC24 Lubricants, greases, release products

Soybean oil

- · Application of the substance / the mixture Lubricant
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Gaither Tool Company

2255 W Morton Ave

Jacksonville, IL 62650

(217) 245-0545

· Emergency telephone number: (217) 245-0545

## 2 Hazard(s) identification

· Classification of the substance or mixture



**GHS09 Environment** 

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS09

- · Signal word Warning
- Hazard-determining components of labeling:

d-limonene

· Hazard statements

Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Reviewed on 05/01/2024 Printing date 05/01/2024

#### Trade name: Super Slick 'Em

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

80 percent of the mixture consists of ingredient(s) of unknown toxicity.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 1 Fire = 1

Other hazards None known

## Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous Components:			
CAS: 8001-22-7	Soybean oil	70-90%	
CAS: 5989-27-5 RTECS: GW 6360000	d-limonene  Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	5-10%	
CAS: 7782-42-5	Graphite ♦ STOT SE 3, H335	5-10%	

### 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness, place patient securely on side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

## 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:

#### 8001-22-7 Soybean oil

TWA Short-term value: 5 mg/m³ Long-term value: 15 mg/m³

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

#### 5989-27-5 d-limonene

TWA Short-term value: 10 mg/m<sup>3</sup>

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure, use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· Eye protection: Goggles recommended during refilling.

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Dark amber

Odor: Mix of orange and oil
 Odor threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range:

Boiling point/Boiling range: 173 °C (343 °F)

· Flash point: 282 °C (540 °F)

· Flammability (solid, gaseous): Not applicable.

(Contd. on page 5)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

Ignition temperature: 255 °C (491 °F)
 Decomposition temperature: Not determined.

• Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

**Lower:** 0.7 Vol % **Upper:** 6.1 Vol %

· Vapor pressure @ 20 °C (68 °F): 2.3 hPa (2 mm Hg)

• **Density @ 20 °C (68 °F):** 1.011 g/cm³ (8.437 lbs/gal)

Relative density
 Vapour density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 10.0 % VOC content: 10.0 %

• Other information No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Stable under normal conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
5989-27-5 d-limonene			
Oral	LD50	4400 mg/kg (rat) Remarks: Behavioral: Change in motor activity (specific assay). Respiratory disorder Skin and Appendages: Other: Hair	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/96 hours	0.72 mg/l (Pimephales) (OECD Test Guideline 203)	

(Contd. on page 6)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

- · Primary irritant effect:
- on the skin:

Irritant to skin and mucous membranes.

May cause an allergic skin reaction.

- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

· · · · · · · · · · · · · · · · · · ·
5989-27-5 d-limonene 3
· NTP (National Toxicology Program)
None of the ingredients are listed.
· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients are listed.

## \* 12 Ecological information

- · Toxicity
- · Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

#### 5989-27-5 d-limonene

EC50 0.36 mg/l (daphnia) (OECD Test Guideline 202)

- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 7)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport information

· UN-Number

· **DOT** Non-Regulated Material

· ADR, IMDG, IATA UN3082

· **UN proper shipping name** Not Regulated for Transportation

• **DOT** Non-Regulated Material

· ADR UN3082 Environmentally hazardous substances, liquid, n.o.s.

(Dipentene)

· IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (DIPENTENE), MARINE POLLUTANT

IATA ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (DIPENTENE)

· Transport hazard class(es)

· DOT

· Class Non-Regulated Material

· ADR



• Class 9 (M6) Miscellaneous dangerous substances and articles

· Label

· IMDG, IATA



· Class 9 Miscellaneous dangerous substances and articles

· Label

· Packing group

· DOT

· ADR, IMDG, IATA

· Environmental hazards: Product contains environmentally hazardous substances: d-

Non-Regulated Material

limonene

Special marking (ADR):
 Special marking (IATA):
 Symbol (fish and tree)

• Special precautions for user Warning: Miscellaneous dangerous substances and articles

Danger code (Kemler):

(Contd. on page 8)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

· **EMS Number:** F-A,S-F

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

·IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 5L
 Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN3082, Environmentally hazardous substances, liquid, n.o.s.

(Dipentene), 9, III

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients are listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 9)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Printing date 05/01/2024 Reviewed on 05/01/2024

Trade name: Super Slick 'Em

### · Hazard pictograms





GHS07 GHS09

### · Signal word Warning

#### Hazard-determining components of labeling:

d-limonene

#### · Hazard statements

Causes skin irritation.

May cause an allergic skin reaction.

Toxic to aquatic life with long lasting effects.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves.

Avoid release to the environment.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If on skin: Wash with plenty of water.

Collect spillage.

Take off contaminated clothing and wash it before reuse.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

· State Right to Know	State Right to Know		
CAS: 8001-22-7	Soybean oil	70-90%	
CAS: 5989-27-5 RTECS: GW 6360000	d-limonene  Flam. Liq. 3, H226; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Skin Sens. 1, H317	5-10%	
CAS: 7782-42-5	Graphite  ♦ STOT SE 3, H335	5-10%	
All ingredients are liste	d.		

<sup>·</sup> Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### \* 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 02/27/2015 / 2

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 04.

Reviewed on 05/01/2024 Printing date 05/01/2024

Trade name: Super Slick 'Em

### · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

### \* Data compared to the previous version altered.

SDS created by MSDS Authoring Services www.msdsauthoring.com (877) 204-9106