



SAFETY DATA SHEET

Issuing Date 21-Nov-2023

Revision Date 07-Sep-2024

Revision Number 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Ru-Glyde

Other means of identification

Product Code(s) RG-18, RG-18BK, RG-18CT, RG-18MY, RG-20, RG-20BK, RG-20MY, RG-55, RG-55BK, RGC-18, RGC-20

Synonyms Tire Mounting Lubricant

Recommended use of the chemical and restrictions on use

Recommended Use Tire Mounting and Rubber Lubricant

Uses advised against No information available

Supplier's details

Supplier Address

AGS Company
Automotive Solutions LLC
P.O. Box 729
Muskegon, MI
49443
TEL: 800-253-0403

Emergency telephone number

Emergency Telephone Number 800-255-3924

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word	Warning
-------------	---------

Hazard Statements

- Causes skin irritation
- Causes serious eye irritation

**Appearance** Tea colored.**Physical State** Liquid.**Odor** Odorless.**Precautionary Statements****Prevention**

- Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- None

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation occurs: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.

Storage

- None

Disposal

- None

Hazard Not Otherwise Classified (HNOC)

Not applicable.

Other information

Harmful to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms**

Tire Mounting Lubricant

Chemical Name	CAS-No	Weight %
Potassium hydroxide	1310-58-3	1.78
Ethylene glycol	107-21-1	1.28

4. FIRST AID MEASURES**Description of necessary first-aid measures****Eye Contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation persists.

Skin Contact	Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. Remove and wash contaminated clothing before re-use.
Inhalation	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if exposed or you feel unwell.
Ingestion	Rinse mouth. If symptoms persist, call a physician.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms/effects, acute and delayed**Most Important Symptoms/Effects** Irritation.**Indication of immediate medical attention and special treatment needed, if necessary****Notes to Physician** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None**Specific Hazards Arising from the Chemical**

Containers may explode when heated.

Hazardous Combustion Products Sodium oxides. Potassium oxides.**Explosion Data****Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** None.**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions** Use personal protective equipment. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling.**Environmental Precautions****Environmental Precautions** See Section 12 for additional Ecological Information. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Collect spillage. Dispose of contents/container to an approved waste disposal plant.**Methods and materials for containment and cleaning up****Methods for Containment** Dike far ahead of liquid spill for later disposal.**Methods for Cleaning Up** Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Use personal protective equipment. Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly.**7. HANDLING AND STORAGE**

Precautions for safe handling

Handling Ensure adequate ventilation. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Avoid breathing vapors or mists. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.

Incompatible Products Hydrazine, Acids, Halogenated compounds, Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Ethylene glycol 107-21-1	STEL: 50 ppm vapor fraction STEL: 10 mg/m ³ inhalable particulate matter, aerosol only TWA: 25 ppm vapor fraction	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-
Triethanolamine 102-71-6	TWA: 5 mg/m ³	-	-
Sodium dichromate, dihydrate 7789-12-0	STEL: 0.0005 mg/m ³ Cr(VI) inhalable particulate matter TWA: 0.0002 mg/m ³ Cr(VI) inhalable particulate matter S*	TWA: 5 µg/m ³ Action Level: 2.5 µg/m ³ Cr (vacated) Ceiling: 0.1 mg/m ³ Ceiling: 0.1 mg/m ³ CrO ₃ applies to any operations or sectors for which the Hexavalent Chromium standard [29 CFR 1910.1026] is stayed or is otherwise not in effect	IDLH: 15 mg/m ³ Cr(VI) TWA: 0.0002 mg/m ³ Cr
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0	TWA: 5 mg/m ³ , as oil mist, mineral STEL: TWA: 10 mg/m ³ , as oil mist, mineral	TWA: 5 mg/m ³ , as oil mist, mineral	-
Citral 5392-40-5	TWA: 5 ppm inhalable fraction and vapor S*	-	-

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Tightly fitting safety goggles.
Skin and Body Protection Protective gloves.
Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid.	Appearance	Tea colored.
Odor	Odorless.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	9.6	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	100 °C / 212 °F	None known
Flash Point	No data available	None known
Evaporation rate	Slower than Butyl Acetate	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	Heavier than air	Air = 1
Specific Gravity	1.01	None known
Water Solubility	Completely soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties No data available.

Explosive Properties No data available

Oxidizing Properties No data available

Other information

VOC Content (%) 0.13

10. STABILITY AND REACTIVITY**Reactivity**

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

None known based on information supplied.

Incompatible materials

Hydrazine, Acids, Halogenated compounds, Strong oxidizing agents.

Hazardous decomposition products

Sodium oxides. Potassium oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	There is no data available for this product
Inhalation	Vapors may irritate throat and respiratory system.
Eye Contact	Causes serious eye irritation.
Skin Contact	Causes skin irritation.
Ingestion	Ingestion may cause irritation to mucous membranes.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	90 mL/kg (Rat)	-	-
Cocos nucifera oil	> 5000 mg/kg (Rat)	-	-
Potassium hydroxide	= 214 mg/kg (Rat)	-	-
Ethylene glycol	4000 mg/kg (Rat)	9530 µL/kg (Rabbit)	-
Triethanolamine	= 4190 mg/kg (Rat)	> 20000 mg/kg (Rabbit) > 16 mL/kg (Rat)	-
Sodium dichromate, dihydrate	= 50 mg/kg (rat)	= 960 mg/kg (Rabbit)	= 0.124 mg/l (rat) 4 hr.
Petroleum distillates, solvent dewaxed heavy paraffinic	> 15000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	>4.7 mg/l (rat) 4 hr.
Citral	= 4960 mg/kg (Rat)	= 2250 mg/kg (Rabbit)	-
(r)-p-mentha-1,8-diene	= 4400 mg/kg (Rat) = 5200 mg/kg (Rat)	> 5 g/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Irritation

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available
Mutagenic Effects No information available
Carcinogenicity Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene, DMSO). These carcinogenic components are typically found in crude petroleum products and are removed through the refinement process.

Reproductive Toxicity No information available
Developmental Toxicity No information available
STOT - single exposure No information available
STOT - repeated exposure No information available
Aspiration Hazard No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 11650 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Potassium hydroxide 1310-58-3		LC50 96 h: = 80 mg/L static (Gambusia affinis)		
Ethylene glycol 107-21-1	EC50 96 h: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: 14 - 18 mL/L static (Oncorhynchus mykiss) LC50 96 h: 40000 -	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50 48 h: = 46300 mg/L (Daphnia magna)

		60000 mg/L static (Pimephales promelas) LC50 96 h: = 16000 mg/L static (Poecilia reticulata) LC50 96 h: = 27540 mg/L static (Lepomis macrochirus) LC50 96 h: = 40761 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 41000 mg/L (Oncorhynchus mykiss)		
Triethanolamine 102-71-6	EC50 96 h: = 169 mg/L (Desmodesmus subspicatus) EC50 72 h: = 216 mg/L (Desmodesmus subspicatus)	LC50 96 h: 10600 - 13000 mg/L flow-through (Pimephales promelas) LC50 96 h: 450 - 1000 mg/L static (Lepomis macrochirus) LC50 96 h: > 1000 mg/L static (Pimephales promelas)		EC50 24 h: = 1386 mg/L (Daphnia magna)
Sodium dichromate, dihydrate 7789-12-0		LC50 96 h: = 213 mg/L static (Lepomis macrochirus) LC50 96 h: = 33.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 69 mg/L flow-through (Oncorhynchus mykiss)		EC50 48 h: 0.098 - 0.129 mg/L (Daphnia magna) EC50 24 h: = 1.4 mg/L (Daphnia magna)
Petroleum distillates, solvent dewaxed heavy paraffinic 64742-65-0		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)
Citral 5392-40-5	EC50 72 h: = 16 mg/L (Desmodesmus subspicatus) EC50 96 h: = 19 mg/L (Desmodesmus subspicatus)	LC50 96 h: 4.6 - 10 mg/L static (Leuciscus idus)	EC50 = 2100 mg/L 30 min	EC50 48 h: = 7 mg/L (Daphnia magna)
(r)-p-mentha-1,8-diene 5989-27-5		LC50 96 h: 0.619 - 0.796 mg/L flow-through (Pimephales promelas) LC50 96 h: = 35 mg/L (Oncorhynchus mykiss)		

Persistence and Degradability No information available

Bioaccumulation

Chemical Name	Log Pow
Potassium hydroxide	0.83
Ethylene glycol	-1.93

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material may be a hazardous waste under 40 CFR 261, when discarded.

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated.

ICAO Not regulated

IATA	Not regulated.
IMDG/IMO	Not regulated
RID	Not regulated
ADR	Not regulated
ADN	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Contact supplier for inventory compliance status
DSL/NDSL	Contact supplier for inventory compliance status

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylene glycol	107-21-1	1.28	1.0
Sodium dichromate, dihydrate	7789-12-0	0.07	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium hydroxide	1000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Potassium hydroxide	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Ethylene glycol	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Ethylene glycol	107-21-1	Developmental
Sodium dichromate, dihydrate	7789-12-0	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Potassium hydroxide	X	X	X		

Sodium dichromate, dihydrate	X	X	X	X	X
Ethylene glycol	X	X	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA **Health Hazard** 2 **Flammability** 0 **Instability** 0 **Physical and Chemical Hazards** -

HMIS **Health Hazard** 2 **Flammability** 0 **Physical Hazard** 0 **Personal Protection** X

**Indicates a chronic health hazard.*

Prepared By Product Stewardship
 23 British American Blvd.
 Latham, NY 12110
 1-800-572-6501

Issuing Date 21-Nov-2023
Revision Date 07-Sep-2024
Revision Note (M)SDS sections updated: 3. 4. 11.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet