



• Easier • Faster • Safer

Get an immediate ROI with simultaneous improvement in both productivity and safety.



Rotatruck® vs. Handtruck

Leverage Plus™

The smaller Rotacaster wheel at the front gives the Rotatruck greater leverage than traditional 2-wheelers, making it easier to pull back, park, lever and balance loads.

More leverage, less effort

32% less pull-back effort
55% less general handling effort



Easier pull-back effort
& no need to park at waypoints.



Parking and pulling back loads at waypoints increases strain on musculoskeletal structure.

Hands Free Balance™

The Rotatruck's compact, multi-directional wheel base fully supports loads without operator input. No need to park or pull back loads as frequently.

Just push, don't carry

0kg load to carry



The Rotatruck carries the load, not the operator.




Constant operator input to maintain load balance exerting strain and effort.

Magic Step Up™


The fixed orientation of the Rotacaster wheel allows you to step and lever loads instead of turning and reversing (over obstacles), with 78% less effort and 63% faster.

Lever, don't lift

78% less lifting effort
63% faster negotiating kerbs



Up kerbs or over obstructions without reversing.



Maximum effort required to reverse and pull load up a kerb.

Dual Gas Cylinder Rotatruck™

The Dual Gas Cylinder Rotatruck is the easiest, quickest and safest way to handle multiple large heavy gas cylinders. Its ergonomic design eliminates bending and minimises user effort.



Self-Supporting Wheel Base

Self-supporting **multi-directional** Rotatrucks are based on a **highly manoeuvrable** four wheeled base that increases productivity.



Cast Aluminium Nose

Large 303mm x 355mm **cast aluminium** nose for single or multiple loads



Cylinder Kit

For secure handling of multiple cylinders. Available in a high position for large cylinders and a low position for smaller cylinders.



Load Magnets

Magnets secure the load to frame and minimise the need for user input when loading and unloading.



Safety Strap

A **Safety Strap** minimises cylinder movement when transporting for increased load security.



Puncture Proof Rear Wheel

Puncture proof **Microcell foam rear wheels** navigate with ease through rough surfaces.



PRODUCT CODE: 11-23G2

Load Capacity: 230kg
Dimensions: 1700 x 500 x 600mm
Weight: 18kg

COMPONENTS

- Extended hi-strength curved frame
- Double loop handle
- Large 355x305mm aluminum nose
- 250mm puncture proof foam filled rear wheels
- R3 triple 125mm front wheels
- Safety Strap
- 2 Load Magnets

Used by  **BOC**
A Member of The Linde Group

 **Linde**  **AIR LIQUIDE**
ADVANCED BUSINESS & TECHNOLOGIES

 **SUPAGAS**
100% AUSTRALIAN