

Quicker

Safer






#### Winner

Best solution to an identified workplace health and safety issue

#### **Comparative Report**

Rotatruck vs standard hand truck. Download study detailing the ergonomic safety and productivity advantages of the Rotatruck. www.rotacaster.com.au



#### **Quality Components**



## rotaca/ter



#### **MAGLINER®**

Magliner, lightweight, corrosion resistant aluminium handles, frames and toes.

Magliner is a registered trademark of Magline, Inc





Distributor

www.rotacaster.com.au


1 300 768 222

rotacaster.com.au



the ultimate in manoeuvrability


**Reduced effort** as Rotatruck carries the load, not the operator.




**Fully supports load** on configurable multi directional wheel base.



Easier pull-back effort and no need to park at waypoints.



Lever rather than lift load up curbs or over obstructions without reversing.



**Balance rather than carry** the load over soft or uneven terrain.



**Fully supported rotation** allows easy manoeuvrability in confined spaces.

**Rotatruck Benefits** 

Easier

Safer

Quicker



**Easy navigation** doorways and intercoms.







Distributor

www.rotacaster.com.au



## Rotatruck vs. Handtruck




Easier pull-back effort
And no need to park at waypoints.

#### **Pull-backs**




Need to park and pull-back loads at waypoints increasing strain on musculoskeletal structure.



Reduced effort
The Rotatruck carries the load, not the operator.


# Load support

Requires constant operator input to maintain load balance exerting strain and effort.




**Lever rather than lift**Up curbs or over obstructions without reversing.

#### **Curbs & Obstructions**



Operator exerts maximum effort to reverse and pull load up and over curb.




Balance rather than carry
The load over soft or uneven terrain.

Download full comparative report Rotatruck vs Handtruck

www.rotacaster.com.au

**Soft Uneven Terrain** 



Operator carries increased share of load to safely move across terrain.



Distributor

www.rotacaster.com.au


1 300 768 222

rotacaster.com.au





# Rotatruck Set-Up

## Set-up the recline angle to suit the load









Low, heavy load

Regular Load

Tall load

Tall, shallow load

#### Select the wheelbase to suit your needs










Stairclimber (RTSC)

## Select Rotatruck Axle Mounts to optimise set-up







Configuration and application options

Rear Wheel Size		Axle hole/Recline angle				Mounts			
	А	В	С	D	Е	F	01	02	03
125mm				40°				~	
200mm	45°	40°	38°	-	32°	37°	<b>✓</b>	~	~
250mm	40°	35°	32°	-	27°	32°	<b>~</b>	~	~
300mm	35°	30°	28°	-	-	-	<b>~</b>	~	~
Stairclimber	-	38°	36°	-	-	-	<b>~</b>		





Distributor


www.rotacaster.com.au





## **Rotatruck Conversion Kits**





**Convert your existing handtruck** Rotacaster conversion kits are compatible with most modular handtrucks and can be adapted to others, making the conversion to a Rotatruck simple and cost effective.

Rotatruck Conversion Kits	Part Number	/R2	/R3
Basic conversion kit (excludes rear wheels and axle)	12-2301/R_	200Kg	230Kg
4xRC 125mm Rotacaster	12-2312/R_	200Kg	230Kg
8"/200mm balloon cushion	12-2314/R_	200Kg	230Kg
8"/200mm balloon Cushion	12-2315/R_	200Kg	230Kg
10"/250mm balloon cushion	12-2316/R_	200Kg	230Kg
10"/250mm foam filled	12-2325/R_	200Kg	230Kg
RTSC 125mm Rotatruck Stairclimber	12-2360/R_	200Kg	230Kg





Distributor

www.rotacaster.com.au

1 300 768 222

rotacaster.com.au



## **Typical Rotatruck**



Wheelbase: R3 Rotacasters with 250mm foam filled rear wheels, standard frame, extended vertical loop handle.

11-2325-16/R3

Height: 1525mm

Alternate Hi-Stress Frame 11-2325-36/R3 Alternate Curved Frame 11-2325-56/R3



Wheelbase: R3 Rotacasters with 250mm balloon cushion rear wheels, standard frame extended vertical loop handle.

Height: 1525mm Alternate Hi-Stress Frame 11-2316-36/R3

11-2316-16/R3



Wheelbase: R3 Rotacasters with R3 Stairclimber wheel set, standard frame, extended vertical loop handle. Height: 1525mm

11-2360-16/R3

Alternate Hi-Stress Frame 11-2360-36/R3 Alternate Curved Frame 11-2360-56/R3



Wheelbase: R3 Rotacasters with 200mm rubber on cast aluminium rear wheels, standard frame, standard loop handle, Height: 1270mm

11-2314-10/R3

Alternate Hi-Stress Frame 11-2314-30/R3 Alternate Curved Frame 11-2314-50/R3



4xRC R3 Rotacasters, standard frame, standard vertical loop handle. Height: 1330mm

11-2312-13/R3

Alternate Hi-Stress Frame 11-2312-33/R3 Alternate Curved Frame 11-2312-53/R3



Wheelbase: R3 Rotacasters with 200mm balloon cushion rear wheels, standard frame, extended vertical loop handle. Height: 1525mm

11-2315-16/R3

Alternate Hi-Stress Frame 11-2315-36/R3 Alternate Curved Frame 11-2315-56/R3

All trucks shown with cast 457x190mm toe. All trucks available with R2 or R3 Rotacasters. Capacity: R3-225kg/500lb R2-200kg/440lb.

#### Optional Accessories



Wide Load Wings 14-3075



Safety Strap 11-9001



Keg Hook 14-3070/B 100mm 14-3071/B 125mm



Extended Double Verticle Loop Handle 14-3014



Extruded Toe 14-3049 457x228mm 14-3051 508x305mm



Crate latch system



Distributor

www.rotacaster.com.au





# **Special Application Rotatrucks**



#### Wide-load

FF250 fitted with 14-3075 wide load wings	11-2325-17/R3
BC250	11-2316-17/R3
4xRC	11-2312-17/R3
RTSC	11-2360-17/R3



#### Milk crate

FF250 ffitted with milk crate latches	11-2325-43/R3
BC250	11-2316-43/R3
4xRC	11-2312-43/R3
RTSC	11-2360-43/R3



FF250 fitted with bread crate latches	11-2325-61/R3
BC250	11-2316-61/R3
4xRC	11-2312-61/R3
RTSC:	11-2360-61/R3



Mu	lti-	load

FF250 Multi-load: fitted with two 14-3050 toes	11-2325-18/R3
BC250	11-2316-18/R3
4xRC	11-2312-18/R3
RTSC	11-2360-18/R3



FF250 itted with 14-3071/B keg hook	11-2325-59/R3
BC250	11-2316-59/R3
4xRC	11-2312-59/R3
RTSC	11-2360-59/R3



FF250 fitted with 14-3070/B keg hook	11-2325-56/R3
BC250	11-2316-56/R3
4xRC	11-2312-56/R3
RTSC	11-2360-56/R3

All trucks available with R2 or R3 Rotacasters. Capacity: R3-225kg/500lb R2-200kg/440lb.



Wheelbase: FF250 All-Terrain/R3



Wheelbase: BC250 All-Terrain/R2



Wheelbase: 4xRC Rotacaster/R3



Wheelbase: BC200 All-Terrain/R2



Wheelbase: CA200 All-Terrain/R2



Wheelbase: Rotatruck Stairclimber/R2



Distributor

www.rotacaster.com.au





## **Build Your Own Rotatruck**

Configure your Rotatruck	Select Wheelbase	Frames
4xRC 125mm Rotacaster (RC)	2312	if
8"/200mm rubber on cast aluminum wheels	2314	MAGUNED
8"/200mm balloon cushion wheels	2315	
10"/250mm Balloon Cushion with Wheel Set	2316	
10"/250mm Foam Filled with Wheel Set	2325	
Self-supporting Stairclimber	2360	
RTSC Self-supporting Stairclimber	2361	

Handle/Overall Height	Тое
Standard Loop/1270mm	457x190 Cast
H	457x228 Extruded
H	508x305 Extruded
Vertical Loop/1320mm	457x190 Cast
	457x228 Extruded
	508x305 Extruded
Extended Vertical Loop/1525mm	457x190 Cast
	457x228 Extruded
H	508x305 Extruded
Double Vertical Loop/1575mm	457x190 Cast
	457x228 Extruded
	508x305 Extruded

Standard	Hi-Stress	Curved			
Fra	Frame Combination				
10	30	50			
11	31	51			
12	32	52			
13	33	53			
14	34	54			
15	35	55			
16	36	56			
17	37	57			
18	38	58			
19	39	59			
20	40	60			
21	41	61			

Enter part number segments to create item number.





Distributor

www.rotacaster.com.au

1 300 768 222

rotacaster.com.au



Rotacasters

3