				_	PRODUCT PROPERTIES	PROPERT	IES						
PRODUCT DESCRIPTION	Shore A Hardness ±5	Operating Temp C Min. Max.	Application Temp C Min. Max.	Tensile Strength Mpa (ISO 8339)/(ISO37)	Shear Strength Mpa (ASTMD 1002)	Paintable (Tests are recommended)	Colours Available	Elongation at Break (%) (ASTMD 1002)	Skin Time (Minutes) (23°C & 50% R.H)	Cure Rate (mm per 24hrs) (23°C & 50% R.H)	Dynamic Movement (%)	Package Size (mL)	Part number: Fix (Product Number) (Product Difference) (Colour) (Package in Litres: eg 300mL = L03 or 600mL = L06
FIX8 Synthetic Adhesive Silicone	40	-40+100	5 to 30	1.00	1.00	NO	BK, WH, AW	>300	40	ω	25	300 Cart	FIX8L_
FIX8 FN Finishing Adhesive Silicone	35	-40 +100	5 to 30	1.00	1.00	NO	ALU, TRANS	>100	10	ω	12.5	300 Cart	FIX8FN03
FIX8 HT - MOQ APPLIES High Track Adhesive Silicone	50	-40+100	5 to 30	1.00	1.80	NO	BK, WH	>80	20	4	12.5	300 Cart 600 Foil	FIX8HTL_
FIX15 Multipurpose Adhesive Sealant	48	-40 +100	5 to 30	2.20	1.60	YES	BK, WH, GY	>300	15	ω	25	290 Cart 600 Foil	FIX15L
FIX190 High Strength Adhesive Sealant	45	-40+100	5 to 30	3.60	1.60	YES	BK, WH	>230	45	ω	20	600 Foil	FIX190L_
FIX190HT High Strength Adhesive Sealant	45	-40+100	5 to 30	3.60	1.60	YES	BK, WH	>230	12	4	20	290 Cart 600 Foil	FIX190FWTL_
FIX200 POLYMER & GLASS Flexible Adhesive Silicone	25	-40 +100	5 to 30	0.75	0.75	NO	Ŗ	600	30	_	50	310 Cart	FIX200BKL03
FIXCLEAR 100% Clear Adhesive Sealant	40	-40 +100	5 to 30	1.00	1.00	YES	Clear	>230	12	4	20	290 Cart	FIXClearL03
													FIVOTO

_
6
VOWE dild
=
~
-
_
UVE
α
_
7
7
7
_
_
_
_
_
_
_
_
_
_
_
I I I I I I I I I I
I I I I I I I I I I
IIIIIIIIII
IIIIIIIIII
IIIII Ule WO
TITLI UTE WOLKING
IIIII Ule WO

MP101 Extra Fine White 2K Filler	FM30 FUEL MASTER FAC240 Specialist Fuel Tank Adhesive Sealant	FIX1 DC TEAK DECK CAULKING Improved Chemical Cleaner Resistance Teak and Cork Deck Caulking	FIX30 Universal Construction, Floor & Tile Adhesive Sealant	FIX3 Synthetic Flooring Bonding Adhesive	FMP100 & FMP200 FIXIT Structural Rigid Timber & Foam Core Bonding	FIXCLEAR 100% Clear Multipurpose Adhesive Sealant	FIX200 POLYMER & GLASS Polymer Window Silicone	FIX190 Structural Exterior / Interior & Glass Bonding & Sealing	FIX15 Multipurpose Exterior /Interior Bonding & Sealing	FIX8, FIX8 FN, FIX8 HT Structural Silicone RTV-1 Bonding &Finishing. (Anti-mould)	PRODUCT DESCRIPTION	
*	~				2	2		2	ح		Above & Below Waterline	
						۷	2	2	ح	2	Glazing Fixing & Finishing	
	~		~	2	~	2		~	2	2	Structural Fixing & Finishing	
		2		2			~	~	2	2	UV Stable Non-Yellowing White	RECO
2	~	2	~	~	**	~	2	~	۷	2	All Metals, Fiberglass	RECOMMENDED APPLICATIONS
~	~	~	~	~		~	~	2	~	~	Aluminium & Stainless Steel	DED APPL
							*				*Polymer Window	ICATION
		~		~			~	2	2	~	External Exposed Wipes	S
~		~	~	~	~	~	~	2	~	~	All Timber Types May Require Primer	
				~				2	~	~	Deck Gear & Fitting Seals	
								2	~		Deck to Hull Cabin Tops etc.	
		~									Teak Deck Caulking	
			~								Teak Deck Adhesion	
				~							Synthetic Deck Adhesion	
	~										100% Fuel & Solvent Resistant	

- * * * * * * Polymer window means window made from acrylic or polycarbonate MP101 must be coated with marine paint for below waterline application. One component must be porous such as timber or structural foam care Etch prime aluminium before bonding

















**



Technical Assistance:

Fixtech Pty Ltd,
Unit 1, 20 Export Drive, Molendinar, QLD 4214.
P.O. Box 568, Southport, QLD 4215 AUSTRALIA
Ph.: +61 [7] 5530 1099 (Overseas)
Ph: 1300 887 077 (Australia wide)
Email: info@fixtech.com.au

Fixtech International Limited, Taiwan Branch
96 hongping Road, Siaogang, Kaohsiung City, 812 TAIWAN
Ph: +886 (7) 8062506 Fx: +886 (7) 8062811
Email: infotw@fixtech.asia

Fixtech International Limited, Zhuhai (Southern & Central China)
3rd F, Building 8, No.1 Pingdong Road, Nanping Technology Park,
Zhuhai City 519060, Guangdong, CHINA
Ph: +86 756 7750077 Fx: +86 756 8513101
Email: sales@fixtech.com.cn



As a general guideline, to achieve successful adhesion, abrade and clean with Industrial Alcohol and ensure that the surface is dry and clean before adhering with Fixtech products. For further details, including TDS, MSDS and application hints and tips, please refer to our website: www.fixtech.com.au

days.	
er 7 o	
d afte	
achieved	
strength)
perty	
pro	
∄.	
hours	
after 6	
diesel	
nersed in	
/ imr	
oe fully	
can	
**FM30	

FMP100 Fixlt Strongest One Part Gel 100% Waterproof Adhesive	n/a	-40 +	5 to 35	10.00	12.00	YES	Transp	n/a	30	initial 24hr	n/a	310 Cart	FMP100
FMP200 FixIt Strongest One Part Liquid 100% Waterproof Adhesive	n/a	-40 + 100	5 to 35	10.00	12.00	YES	Transp	n/a	30	2hr initial 24hr	n/a	750 Bottle	FMP200
FIX3 Synthetic Decking Bedding Adhesive	40	-40+ 100	5 to 30	1.00	1.00	ON N	Teak	250	40	м	25	600 foil	FIX3FBTKL06
FIX30 Universal Floor & Tile Bonding Adhesive Sealant	n/a	-40 + 100	5 to 30	>0.75	>0.75	YES	WH	300	40	1.5	20	600 foil	FIX30WHL06
FIXIDC TEAK DECK CAULKING* Cork, Teak, Synthetic Decking	37	-40 + 100	5 to 30	>1.0	>1.0	Q N	GY BK	330	30	ო	25	300 Cart 600 Foil	FIXIDCL_
FM30 FUEL SEALANT** US Approved Fuel Resistant	09	-54 +	5 to 35	>2.0	>2.0	YES	DK Grey	>200	30 6 Hr fill	2 pack	20	1kg	FAC240PSL05
MP101 Extra Fine Poly White 2K Filler	78	-30 + 115	5 to 25	n/a	n/a	YES	White	n/a	5	30	n/a	1kg inc Activator	MP101

FIX 8

300mL

Structural Adhesive Silicone

(Available: White, Antique White, Black)

- · Structural bonding of most substrates
- Suitable for marine exposure Above waterline bonding including
- synthetic decking
- Can be used for under waterline screw fitting seals
- Medium modulus stays flexible
- Weatherproof and U.V. resistant
- Cannot be stained or painted over
- 600ml MOQ applies




300mL

Expert Finishing Silicone

(Available: Aluminium and Translucent with anti mould)

- Smooth to apply and bonds to most substrates Suitable for above waterline marine exposure
- Weatherproof and U.V. resistant
- Suitable for acid rain zones
- Excellent smooth shiny finishing
- Medium modulus stavs flexible





Fix 8 Fix 8 Fix 8

산들 산들 산들

M. C. C. M. C. C.

FIX8HT

300mL

Structural Silicone RTV-1 Thixotropic structural bonding

(Available: White & Black with anti mould.)

- Structural bonding of most substrates
- Good green strength to hold before cure
- Suitable for marine exposure
- Suitable panel and direct glass bonding
- Above waterline bonding and interior bonding
- Can be used for under waterline screw fitting seals
- High modulus and high shore A hardness
- Weatherproof and U.V. resistant
- Cannot be stained or painted over
- 600ml MOQ applies



FIX15

290mL

Multipurpose Exterior /Interior Bonding & Sealing

(Available: Black, White, Grey)

- · All fittings, fixtures and fastenings
- UV stable, age resistant & weatherproof
- Thru hull fittings
- Primerless adhesion to many
- No bubbles for perfect finish
- Waterproof sealing and wipes Saves time and costs
- Paintable when wet
- and flow coat after 2 hours
- Bond above and below water

FIX190, FIX 190HT

290mL

Structural Exterior / Interior & Glass Bonding & Sealing

(Available: White and Black. Std & Fast) Primerless adhesion to many surfaces

- Bonding to all structural foam core materials
- Structural bondina Fly-bridge & Deck to Hull
- UV Stable, age resistant and weatherproof
- Direct glazing bonding & sealing Bonding components, panels etc. (PP blend fiberglass & aluminium)
- Drinking water safe
- Waterproof sealing and wipes • Excellent impact resistance
- Thru hull fittings
- Bond above and below water



310mL

Polymer Window Silicone (Available: Black)

- Ideal for Acrylic, Polycarbonate and Glass profiles
- Structural bonding & sealing Primerless adhesion to many surfaces
- · UV stable, age resistant and weatherproof



FIXCLEAR

290mL

100% Clear Multipurpose **Adhesive Sealant**

- · Mirrors, veneer panels, LED and optic fibre lighting
- Insulation and internal bonding
- 100% waterproof



FIX3

(Available: Teak)

Good flexibility

MOQ applies

FIX30

(Available: White)

Synthetic Flooring Bonding Adhesive

• Primerless adhesion to many surfaces

• Excellent shock and sound absorption • Waterproof, weatherproof, UV stable

• Bonding Teak Deck, Stone & Ceramic Tiles

Good working time, fast strength build-up

• Walk on in 12 hours, no bubble formation

Excellent shock and sound absorbance

Primerless adhesion to many surfaces

Age resistant and waterproof

• No fasterners required

• Bonding Flexiteek, Composite PVC, Cork deck etc.

• Suitable working time, excellent bonding performance.

FM30 FUEL MASTER FAC240

500mL

Specialist Fuel Tank Adhesive Sealant

- Thru tank fittings
- Internal baffle bonding
- Lids and inspection hatch bonding
- 5m head pressure tested



MP101 EXTRA FINE WHITE 2K FILLER

(Available: White with Red activator)

- 2 pack ultra smooth finishing filler
- Quick to cure and 30 minute sandable • Ideal for fiberglass, timber, steel and aluminum
- Paintable
- Must be sealed for application below waterline



500mL

Protectant, Polish and Waterless Wash

- Makes up to 7.6 Litres, mixed at a 15:1 ratio
- Can be buffed to a shine
- Safe for use on all surfaces: rubber, metal, plastic, electrical/wiring, wood & motors
- Extends the life of equipment, vehicles. Reduces costs associated with cleaning and maintaining equipment



U-Kote

- Helps to protect vehicles and Equipment from: Road Grime, Asphalt, Bugs, Mud and Salt.



Keep'et Clean **U-Kote**[™] Concentrate Protectant, Polish & Waterless Wash. • Makes up to 7.6 litres @ 15:1 ratio • Helps protect vehicles and equipment from:

- Road Grime, Asphalt, Mud, Salt.
- Can be buffed to a high shine.
- Mist onto the front of the vehicle to help prevent bugs and other road debris from sticking.

• Mist on Wipe Off.

500ML Net

Bottled in Australia by Fixtech Pty Ltd – PO Box 568, Southport, QLD 4125 PH: +61 (0) 7 5530 1099 Email: info@fixtech.com.au



Teak and Cork Deck Caulking (Available: Black, Slate Grey)

• UV Stable, heat, age resistant, waterproof and weatherproof

 Excellent resistance to soap cleaning • Elastic and does not go hard or brittle

• Easy to apply and sand for a

great finish No bubble formation

• Not paintable Slate Grey available in 600ml only



750gm

1 Ltr

(Fixech (Fixec

300mL

600mL

600mL

Universal Construction, Floor & Tile Bonding Adhesive Sealant

FMP100 & FMP200 FIXIT

Structural Rigid Timber & Foam Core

Bonding (Available: Transparent Paste and Honey Liquid)

End grain bonding

• Strong as epoxy One component only

- Clamping required for 1-2 hours only • Fast turn-around time
- All foam core bonding • One component must be porous
- Invisible timber joint
- 100% waterproof also bond wet on wet





(Available: Clear)

Polypropylene Plastic surface bonding primer



