

Fixtech Pty Ltd – PO Box 568, Southport, QLD
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322
Email: info@fixtech.com.au

SAFETY DATA SHEET

Fix200 – FS200

1. Identification

1.1 Identification of the substance or preparation:

Product Name: Fix200, FS200

1.2 Use of substance or preparation:

Adhesive Sealant

1.3 Company undertaking identification:

Fixtech Pty Ltd – Fixtech Marine Solutions
Unit 1/20
Molendinar, Queensland 4214
Tel: +61 7 5530 1099
Fax: +61 7 5530 1322
Email: info@fixtech.com.au

1.4 Emergency telephone:

+61 7 5530 1099

2. Composition/information on ingredients

Ingredients	CAS No.	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Polydimethylsiloxane, hydroxy-terminated	70131-67-8	30-60	Not set	Not set
Calcium carbonate (limestone)	1317-65-3	30-60	10	Not set
Dimethylpolysiloxanes	63148-62-9	10-30	Not set	Not set
Silane, trimethoxymethyl-	1185-55-3	1-5	Not set	Not set
octamethylcyclotetrasiloxane/silica reaction prod	68583-49-3	1-5	Not set	Not set
titanium dioxide	13463-67-7	1-5	10	Not set
Amorphous (fumed) silica	68611-44-9	<4	Not set	Not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

Fixtech Pty Ltd – PO Box 568, Southport, QLD
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322
Email: info@fixtech.com.au

SAFETY DATA SHEET

Fix200 – FS200

3. Hazardous identification

Statement of Hazardous Nature

This product is classified as: Not classified as hazardous according to the criteria of SWA. Not a Dangerous Good according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good under the ADG Code.

UN Number: None allocated

GHS Signal word: NONE. Not hazardous.

PREVENTION

P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P281: Use personal protective equipment as required.

RESPONSE

P337: If eye irritation persists: seek medical attention.

P352: Wash with plenty of soap and water.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P370+P378: Not combustible. Use extinguishing media suited to burning materials.

STORAGE

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

P501: If product cannot be recycled, consider controlled incineration, or contact a specialist waste disposal company (see Section 13 of this SDS).

Emergency Overview:

Physical Description & colour: Black paste.

Odour: Sweet odour.

Major Health Hazards: no significant risk factors have been found for this product.

4. First aid measures

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Fixtech Pty Ltd – PO Box 568, Southport, QLD
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322
Email: info@fixtech.com.au

SAFETY DATA SHEET

Fix200 – FS200

Inhalation: No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

Skin Contact: Gently brush away excess solids. Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

Eye Contact: Quickly and gently brush particles from eyes. No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the product is removed. Obtain medical advice if irritation becomes painful or lasts more than a few minutes. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

5. Fire fighting measures

Fire and Explosion Hazards: There is no risk of an explosion from this product under normal circumstances if it is involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Flash point:	Combustible solid
Auto ignition Temperature:	Not determined
Flammability limits:	Not determined
Flammability class:	Combustible solid

Extinguishing media: Preferred extinguishing media are carbon dioxide, dry chemical, foam, water fog.

6. Accidental release measures

Minor spills do not normally need any special cleanup measures. In the event of a major spill, prevent spillage from entering drains or water courses. Wear full protective clothing including eye/face protection. All skin areas should be covered. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, PVC. Eye/face protective equipment should comprise as a minimum, protective goggles. If there is a significant chance that dusts are likely to build up in cleanup area, we recommend that you use a suitable Dust Mask. Otherwise, not normally necessary. Stop leak if safe to do so, and contain spill. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Consider vacuuming if appropriate. Can be slippery on floors, especially when

Fixtech Pty Ltd – PO Box 568, Southport, QLD
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322
Email: info@fixtech.com.au

SAFETY DATA SHEET

Fix200 – FS200

wet. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

7. Handling and storage

Note: See section 8 for Personal Protective Equipment.

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Check packaging - there may be further storage instructions on the label.

8. Exposure controls/personal protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: **AS/NZS 4501** set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m3)	STEL (mg/m3)
Calcium carbonate (limestone)	10	Not set
titanium dioxide	10	Not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are

for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used where there is ventilation that is adequate to keep exposure below the TWA levels. If necessary, use a fan.

Eye Protection: Eye protection such as protective glasses or goggles is recommended when this product is being used.

Fixtech Pty Ltd – PO Box 568, Southport, QLD
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322
Email: info@fixtech.com.au

SAFETY DATA SHEET

Fix200 – FS200

Skin Protection: You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

Protective Material Types: There is no specific recommendation for any particular protective material type. Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should, if practical, be provided near to where this product is being used.

9. Physical and Chemical Properties

9.1 General information:

Physical Form:	Black Paste
Odour:	Sweet odour
Density:	C.A 1.67 g/cm ³
Viscosity:	Thixotropic Paste
Flash point:	Not applicable
Boiling point:	No specific data. Expected to decompose before boiling.
Explosion limits:	Not applicable
Solubility in other:	Organic solvents
Solubility in water:	Not soluble
pH:	Neutral
Volatile content:	20g/L (1.20% w/w)

Note: the above information is not intended for use in preparing product specifications

10. Stability and reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated.

Incompatibilities: strong acids, strong oxidising agents. Curing releases small quantities of methanol.

Fire Decomposition: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water, silica and other silicon compounds. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product will not undergo polymerisation reactions.

SAFETY DATA SHEET

Fix200 – FS200

11. Toxicological information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

Ingredient

Risk Phrases

No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations.

Potential Health Effects

Inhalation: Short term exposure: Available data indicates that this product is not harmful. However, product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term inhalation.

Skin Contact: Short term exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However, product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term skin exposure.

Eye Contact: Short term exposure: This product may be irritating to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term exposure: No data for health effects associated with long term eye exposure.

Ingestion: Short term exposure: Significant oral exposure is considered to be unlikely. This product, while believed to be not harmful, is likely to cause headache and gastric disturbance such as nausea and vomiting if ingested in significant quantities. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Titanium Dioxide is Class 3 - unclassifiable as to carcinogenicity to humans. See the IARC website for further details. A web address has not been provided as addresses frequently change.

12. Effects on the environment

Insufficient data to be sure of status.

SAFETY DATA SHEET

Fix200 – FS200

13. Disposal considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

14. Transport information

UN Number:

This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

15. Regulatory information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

16. Other information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition Australian Inventory of Chemical Substances
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)

Fixtech Pty Ltd – PO Box 568, Southport, QLD
PH: +61 (0) 7 5530 1099, Fax: +61 (0) 7 5530 1322
Email: info@fixtech.com.au

SAFETY DATA SHEET

Fix200 – FS200

R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.